

Multi flute rougher; 45° helix; DIN6527L; long length; AlCrN coated
 Schruppfräser multi Schneiden; 45° Drallwinkel; DIN6527L; lange Ausführung; AlCrN beschichtet

Specifications / Spezifikationen

NetPRICE

| DIN 6535 HA | DIN 6535 HB | Dc | Ds | Lc | Ln | Dn | Lt | r | z |
|--------------|--------------|------|----|----|----|------|-----|--------|---|
| BLC3L04045RN | BLW3L04045RN | 4,0 | 6 | 11 | 16 | 3,8 | 57 | 21,64 | 3 |
| BLC4L05045RN | BLW4L05045RN | 5,0 | 6 | 13 | 18 | 4,8 | 57 | 21,61 | 4 |
| BLC4L06045RN | BLW4L06045RN | 6,0 | 6 | 13 | 19 | 5,7 | 57 | 21,61 | 4 |
| BLC4L08045RN | BLW4L08045RN | 8,0 | 8 | 19 | 25 | 7,6 | 63 | 28,70 | 4 |
| BLC4L10045RN | BLW4L10045RN | 10,0 | 10 | 22 | 30 | 9,5 | 72 | 38,77 | 4 |
| BLC4L12045RN | BLW4L12045RN | 12,0 | 12 | 26 | 36 | 11,5 | 83 | 52,42 | 4 |
| BLC4L14045RN | BLW4L14045RN | 14,0 | 14 | 26 | 36 | 13,5 | 83 | 63,70 | 4 |
| BLC4L16045RN | BLW4L16045RN | 16,0 | 16 | 32 | 42 | 15,5 | 92 | 85,90 | 4 |
| BLC5L16045RN | BLW5L16045RN | 16,0 | 16 | 32 | 42 | 15,5 | 92 | 92,46 | 5 |
| BLC5L18045RN | BLW5L18045RN | 18,0 | 18 | 32 | 42 | 17,5 | 92 | 99,90 | 5 |
| BLC5L20045RN | BLW5L20045RN | 20,0 | 20 | 38 | 52 | 19,5 | 104 | 137,50 | 5 |
| BLC6L20045RN | BLW6L20045RN | 20,0 | 20 | 38 | 52 | 19,5 | 104 | 139,50 | 6 |

